




MACHINES FOR SPECIAL JOBS



**AVAILABLE BLADES**




**TECHNICAL CHARACTERISTICS**



**ACCESSORIES**



**PACKAGE**



- For bullnosing and beveling. Create 1/2 Bullnose, full bullnose, 45° bevel (Jolly) on: marble, granite, porcelain, single and double fired.
- Maximum length of shaping: 80 cm (31 1/2"). Extend length of shaping up to 120 cm (47 1/4") thanks to the side extensions and table for large materials (accessories).
- Minimum tile width: 4 cm (1 1/2"). Maximum tile width: 60 cm (23 5/8").
- Maximum depth of shaping/radius half bullnose: 30 mm (1 3/16").
- Maximum depth of shaping full bullnose: 22 mm (7/8"); wheel radius: 11 mm (7/16").
- Optional: external tank + pump kit.

- Optional: wheel kit feed.
- Three levels of finishing: rough, finished, polished.
- Gear ratio of motor to wheel 1 ÷ 1.6. Drive belt type poly V.
- Heavy duty water pumps provides superior wheel cooling.
- Supplied with: milling bullnose wheel radius 10 mm (3/8"), universal table, key kit with wrench, dressing stone, user and maintenance manual.

**MODEL SPECIFICATIONS**

Part No.									
<b>427ADV</b>	8024648058928	1	230 V 50 Hz	Single-phase	1,5 HP / 1,1 kW	2800	r. 10 mm	r. 3/8"	4480
<b>427ADV 60</b>	8024648060488	1	230 V 60 Hz	Single-phase	1,5 HP / 1,1 kW	3660	r. 10 mm	r. 3/8"	5370
<b>427ADV USA</b>	8024648060471	1	110 V 60 Hz	Single-phase	1,5 HP / 1,1 kW	3660	r. 10 mm	r. 3/8"	5370
<b>427ADV GB</b>	8024648060464	1	110 V 50 Hz	Single-phase	1,5 HP / 1,1 kW	2800	r. 10 mm	r. 3/8"	4480

**CUTTING SPECIFICATIONS AND MACHINE DIMENSIONS/WEIGHT**

Model	Profile									
<b>BULLDOG ADV</b>		30 mm	1 3/16"	30 mm	1 3/16"	—	80 cm 31 1/2"	75 Kg 165.3 lbs	120x80xh 100 cm 47 1/4"x31 1/2"xh 40"	94 Kg 207.2 lbs
		20 mm	3/4"	20 mm	3/4"	—				
		15 mm	5/8"	15 mm	5/8"	—				
		10 mm	3/8"	10 mm	3/8"	—				
		8 mm	5/16"	8 mm	5/16"	—				
		V45°	—	—	15 mm	5/8"				
		90°	30 mm	1 3/16"	—	—				
	11 mm	7/16"	22 mm	7/8"	—					

